

▲ 1000 V



VDE-Šroubovák - křížový Pozidrive (PZ)

- Dřík: kalený, izolovaný.
- Hrot: ISO 8764-PZ.
- Norma: DIN 7438, IEC 60900:2004

				Obj. č.	
	A mm	B/C mm	A inch		
PZ 0	80	83/27	3 1/8"	0613 633 0	1
PZ 1	80	96/31	3 1/8"	0613 633 1	
PZ 2	100	106/35	4"	0613 633 2	
PZ 3	150	114/38	6"	0613 633 3	



VDE-Šroubovák - nástrčný klíč pro vnější šestihran

- Dřík: kalený, izolovaný.
- Hrot: DIN 475/2.
- Norma: DIN 7445, IEC 60900:2004

				Obj. č.	
mm	A mm	B/C mm	A inch		
5,5	125	96/31	5"	0613 636 055	1
6,0	125	96/31	5"	0613 636 06	
7,0	125	106/35	5"	0613 636 07	
8,0	125	106/35	5"	0613 636 08	
9,0	125	106/35	5"	0613 636 09	
10,0	125	106/35	5"	0613 636 10	
11,0	125	114/38	5"	0613 636 11	
12,0	125	114/38	5"	0613 636 12	
13,0	125	114/38	5"	0613 636 13	



Sada VDE šroubováků pro vnější šestihran

Obj. č. 0613 936 66

	A mm	Obj. č.		A mm	Obj. č.	
5,5	125	0613 636 055	8,0	125	0613 636 08	1
6,0	125	0613 636 06	10,0	125	0613 636 10	
7,0	125	0613 636 07	13,0	125	0613 636 13	